## **T** ③ PLAND 上海布莱斯克石油设备有限公司 Topland Oilfield Supplies Ltd.

## MUD PUMP PRESSURE GAUGES

Type F/D One-piece Shock-resistantPressure Gauge



Type F/D one-piece shock-resistant pressure gauge can display mud pressure value exactly and quickly. It'smainly used for measuring pressure of standpipe on the mud pump in the petroleum fields of drilling, fracturing.controlling blowout, etc. It also can miasure static pressure in operating site. The gauge features excellent clog-proof ability, it can prevent very viscous, large granular, easily crystalline, easily concretionary media fromentering gauge, such as mud.

Type F-F ,Type F-Y one-piece shock-resistant pressure gauge is reformed on the basis of common F typeshock-resistant pressure gauge .Type F-F,Type F-Y use flange connecting and NPT2 female thread for 1502unions connecting separately . Type F-F , Type F-Y can be tailor-made according to demand.

Main technical parameters		Outline size:(mm)
Measurement range (MPa)	0~16、25、40、80、100、120	¢ 127 57
Accuracy	2.5 (≤25MPa) ; 1.6(≥40MPa)	
Ambient temp.	-45℃~+65℃	
Shock situation	Shock shouldn't exceed Grade V.H.4 in GB17214.3.	
Connecting	NPT2(female), NPT2(male), flange type, unions type	

Add: Office 8-1011,Lane 5600, Chuansha Road, Pudong, Shanghai, China Tel: +86-21-50499568 www.toplandoil.com