



- 001-HYDRAULIC MOTOR
- 002-BLADDER ACCUMULATOR
- 003-PRESSURE SENSOR
- 004-BLOCK 1 ASSEMBLY
- 005-BLOCK 2 ASSEMBLY
- 006-PROPORTIONAL VALVE
- 007-BUFFER AMPLIFIER
- 008-1" SAE CODE 62
- 009-2" SAE CODE 62
- 010-2.5" SAE CODE 61

UTILITY	
D	MINIMUM FLOW IS
P	358L/MIN, CONSTANT
R	PRESSURE IS 3000psi.

Class Define		HYDRAULIC FLOW DIAGRAM		TF0079001	
P	PRIME	RT495		MATERIAL	REV. NO.
S	SECONDARY			---	A
M	MAJOR	MARK	PES	DOC RENEWED NO.	SIG
	DESIGN				DATE
	PROCESS				
	CHECKED				
	STANDARD				
X	VERIFIED				
	APPROVED				
PROJECT NO. ---				TOTAL	1 PAGE
WE RESERVE THE PROPRIETARY RIGHT AND COPYRIGHT TO THIS DRAWING. IT MAY NOT BE USED OR MADE AVAILABLE TO THIRD PARTIES WITHOUT INTLEP'S CONSENT.				DATE	2020-10-15