

JQHS-100×6X 型气动绞车 (JQHS-100×6X Pneumatic Winch)

JQHS-100×6X 型气动绞车是一款新型的内置行星传动和全盘式制动型气动绞车，为满足海洋平台的特殊作业要求，该绞车具有断气制动功能，外层绳缆的最大拉力可达 100 kN，护罩采用组合式栅格形式，操作方便，防护安全。

JQHS-100×6X pneumatic winch is a new type of planetary transmission and all built-in brake type pneumatic winch, in order to meet the special operation requirements of offshore platform, the winch has a parking brake function, the maximum tension is outer cable shield 100 kN, using a combined grid form, convenient operation and safety protection.



项 目	技术参数	item	specificaton
型号	JQHS-100×6X	model	JQHS-100×6X
第五层最大提升重量 (kN)	100	fifth Max lifting force (lb)	22485
第一层最大提升重量 (kN)	150	First Max lifting force (lb)	33725
最大绳速 (m/min)	6	Max lifting speed (ft/s)	0.33
额定功率 (kw)	30	Rated power (H.P)	40
额定进气压力	0.8	Air pressure (psi)	116
额定耗气量 (m³/min)	≤25.6	Air consumpiton (scfm)	904
刹车	手动+内置盘刹	brake	Hand brake and auto brake
容绳量 (m)	250	Wire capacity (ft))	950
钢丝绳直径 (mm)	Φ 24	diameter (in)	Φ 0.945
外形尺寸 (mm)	1800×1070×1100	overall dimension (in)	75×42×44
重量 (kg)	2200	weight (lb)	4850