

CEMENTING PLUG



TOPLAND supply Cementing Plugs from high-performance special elastomers and core materials. These Cementing Plugs are specially designed with a positive wiping action to ensure that the casing is clean.

Bottom Plugs: Like the Top Cementing Plug, the fins and tail section provide positive wiping action. Fins also serve as a seal while cementing. The core of the bottom plug also made of special materials such as Plastic, Aluminium or Phenolic depending on the application and well conditions. A rubber diaphragm at the top of the plug ruptures after the plug is seated allowing cement to flow through.

Top Plugs: The Top Cementing Plug is designed to exert continuous pressure on the casing wall. The core is made of special materials such as Plastic, Aluminium or Phenolic depending on the application and well conditions. The tapered base fits the cavity of the top plug initiating a positive seal. A solid rubber top plug is also available.

Why Our Cementing Plug:

1. Professional manufacturer from 1994, 20 years experience;
2. The Cementing Plugs are available in a wide variety of sizes to suit your requirements. Special sizes are available upon request. We manufacture Cementing Plugs in various sizes as below. Special Sizes are also available upon request;
3. Durable quality, fast delivery and API standard, ISO9001 quality control system.

Casing size(in)	Casing weight range		Wiper Fin O.D	
	mm	in	mm	in
4 1/2"	14.14-17.26	9.50-11.60	110	4.331
5"	17.11-35.86	11.50-24.10	122	4.803
5 1/2"	20.83-39.88	14.00-26.80	135	5.315
7"	25.30-56.55	17.00-38.00	170	6.693
7 5/8"	35.72-63.69	24.00-42.00	185	7.283
9 5/8"	53.57-79.62	36.00-53.50	235	9.252
10 3/4"	60.27-97.77	40.50-65.70	260	10.236
13 3/8"	71.43-107.15	48.00-72.00	333	13.110
20"	139.89-197.93	94.00-133.00	498	19.606



BOTTOM PLUG



TOP PLUG


Standard
Top Plug



Standard
Bottom Plug



Non-Rotating
Top Plug



Non-Rotating
Bottom Plug



**CEMENTING
PLUGS**

