



### I. Main Parameters:

Nominal Bore: 31/8" Rated Pressur: 5000psi Material Class: EE-0.5 Working Temperature: PU
Product Specification Level: PSL-3
Working Medium: Oil, Gas, Mud

II. Standard:

API Spec 6A

NACE MR 0175-2003

\*\*CSpecification for Wellhead and Christmas Tree Equipment>>

\*\*CPetroleum and natural gas industries - Materials for use in H2Scontaining environments in oil and gas>>

## III. Test:

Pressure Test as per API Spec 6A Standard Drift Test as per API Spec 6A Standard

## IV. Painting as per standard

- V. Cautions
  1. All Parts should be inspected before assembling
  2. Test after assembly
  3. Inject the body with lubrication grease

# VI. Net Weight: 165Kg approx

准多异角位。 中国 1985年			Manual Gate Valve Jiangsu Sanyi Petroleum		
			不调整工程图比例 修订		
Item	Description			Parts Number	Qty
1	Body			SYPYC 8035-01	1
2	Gate Guide			SYPYC 8035-02	2
3	Gate			SYPYC 8035-03	1
4	Body Bushing			SYPYC 8035-04	2
5	Body Bushing Seal			SYPYC 8035-05	2
6	Retainer Plate			SYPYC 8035-06	2
7	Stem			SYPYC 8035-07	1
8	Bonnet Seal Ring			SYPYC 8035-09 SYPYC 8035-08	1
9	Bonnet			SYPYC 8035-09	1
10	Grease Fitting - ½" NPT			SYPYC 8035-11 SYPYC 8035-10	1
11	Shear Pin			SYPYC 8035-12 SYPYC 8035-11	1
12	Nut - Bonnet			SYPYC 8035-13 SYPYC 8035-12	8
13	Stud - Bonnet			SYPYC 8035-14	8
14	Stem Packing			SYPYC 8035-13	1
15	Packing Gland			SYPYC 8035-16 SYPYC 8035-15	1
16	Stem Adapter			SYPYC 8035-17 SYPYC 8035-16	1
17	Bearing Cap			SYPYC 8035-18 SYPYC 8035-17	1 2
18	O-Ring, Bearing Cap to Stem Adapter O-Ring, Bearing Cap			SYPYC 8035-19 SYPYC 8035-18	
20 19	Grease Cup O-Ring, Bearing Cap to Stem Adapter			SYPYC 8035-20 SYPYC 8035-19	1
21	Bearing Cup			SYPYC 8035-21	1
22	Hand Wheel			SYPYC 8035-22	1
25	Pin, Hand Wheel			SYPYC 8035-25	1
27	Seat Ring			SYPYC 8035-27	2
28	Seat Seal Ring			SYPYC 8035-28	2
	Locking Pin			SYPYC 8035-29	2

3½" 5000psi

586.96 781.19